# sikkens

**WOOD COATINGS** 

# FOR OPTIMUM PROCESSING AND PERFECT SURFACES

This topcoats save time, ensure better results, can be optimally processed and offer more effective protection against weathering influences.



# OPTIMAL APPLICATION FOR EFFICIENT PROCESSES

#### PERFECT SURFACE

- The products are characterised by an excellent levelling.
- Even in a wet condition the products are very transparent and not at all milky. Therefore, you already get an impression of the appearance during application and can immediately correct the possible cloudiness.
- They have minimal microfoam formation.

#### **EFFICIENCY**

- Good blocking stability allows quicker formatting of the wooden components.
- Good sandability and demonstrably quicker drying allow a quick processing of the next coat.
- Low viscosity with unchanging stability.

  Wear of your pump device and spray
  equipment as well as loss due to
  overspraying is therefore reduced.

# CLEARLY PROVEN: TESTS OFFER TANGIBLE PROOF THAT OUR NEW PRODUCTS OFFER TOP-CLASS PROTECTION

#### No more blushing

What happens if the treated wood comes into contact with water after just 20 hours?



**Wood treated with conventional product**Result: the wood blushes, the blushing disappears after a time.



Wood treated with the new CETOL® product Result: no blushing at all.







## PERFECT LOOK AND FEEL FOR F NATURAL SURFACE

If you have high expectations of a natural wooden surface, in which the look and feel are particularly important, then the new translucent top coats by Sikkens Wood Coatings are the right choice. Be it semi matt, semi gloss or matt: you always get even surfaces and a consistent colour result

- Accentuation of the wooden structure thanks to high transparency for a fresh and natural appearance
- Noticeably pleasant feel
- Thanks to the water and raindrop resistance they already have resistance against blushing as soon as 20 hours after application.

#### SUSTAINABLY TESTED

You can rely on the sustainability of our products, as emissions analyses\* have shown: the share of ingredients hazardous to the environment and to health is far below the prescribed standard.

\*Emissions analyses according to the principles of health assessment of building products indoors, published by the Deutschen Institut für Bautechnik (DIBt), as of 2010. Tests were carried out after 3, 7 and 28 days for volatile organic content as well as for aldehydes and ketones, carcinogenic materials and formaldehydes.

sikkens-wood-coatings.com



#### THE TOPCOATS THAT SET THE BENCHMARK

This topcoats save time, ensure better results, can be optimally processed and offer more effective protection against weathering influences.

Improved properties and reliable quality are what characterise CETOL® WF 960, CETOL® WF 965 and CETOL® WF 945. Be it for semi matt, satingloss or matt looks – with our products your wooden surface receives optimum protection, a fresh look and a natural appearance.

Even better: high transparency and a pleasant feel underline the natural aspect of wood, that you can immediately sense. Even easier to process: Thanks to perfect levelling, minimum microfoam formation, good blocking stability and sandability you can very efficiently create a top-class surface. Even more secure: more quickly effective water and raindrop resistance minimises the risk of water stains and protects against damage. Even more durable: greater protection against UV rays, hailstone and temperature fluctuations.

#### Pro tip!

If you want to hide optical defects of the wooden surface, you have the opportunity to use our equalizing primer (Joinery Colour Classics E). Feel free to ask your contact person. They will be happy to advise you.

#### CETOL® WF 960



#### 1K Waterborne midand topcoat, translucent

Semi gloss translucent mid- and topcoat for wooden constructions.

- Excellent durability
- No blushing
- Excellent weather resistance

Main Areas of Use	Wood			
Tintable	Yes		\$ <u>\$</u>	
Application	Spray	<b>*</b>		
Thinner	Water	г		
Certification	EN 927-2			
Colour Shade		Gloss Level @ 60°	Packsize	
Base TC colourless		Semi-gloss (30)	5   / 20   / 120   / 1000	

#### CETOL® WF 945



#### 1K Waterborne midand topcoat, translucent

Matt translucent mid- and topcoat for wooden constructions.

- Excellent durability
- No blushing
- Excellent weather resistance

Main Areas of Use	Wood	Wooden constructions: stable			
Tintable	Yes	Yes			
Application	Spray	Spray application Airmix/Airless			
Thinner	Wate	Water			
Certification	EN 927-2				
Colour Shade		Gloss Level @ 60°	Packsize		
Base TC colourless		Matt (10)	51/201		

#### CETOL® WF 965



## 1K Waterborne mid- and topcoat, translucent

Semi gloss translucent mid- and topcoat for wooden constructions.

- Excellent durability
- No blushing
- Excellent weather resistance

Main Areas of Use	Wood		<u>F</u>	
Tintable	Yes	r in the second		
Application	Spray	Ē		
Thinner	Water			
Certification	EN 927-2			
Colour Shade		Gloss Level @ 60°	Packsize	
Base TC colourless		Semi-gloss (40)	5 l / 20 l	

### **AkzoNobel**

Since 1792, we've been supplying the innovative paints and coatings that help to color people's lives and protect what matters most. Our world class portfolio of brands including Dulux, International, Sikkens and Interpon – is trusted by customers around the globe. We're active in more than 150 countries and use our expertise to sustain and enhance everyday life. Because we believe every surface is an opportunity. It's what you'd expect from a pioneering and long-established paints company that's dedicated to providing sustainable solutions and preserving the best of what we have today - while creating an even better tomorrow. Let's paint the future together.

For more information please visit www.akzonobel.com.







